



Steam container

STEAMMASTER MDC 2.600

ArtikelNr.: HM2000000232



Your advantages

- **Completely self-sufficient steam center**
- **Compact design**
- **Integrated 2-fuel burner**
- **Immediately ready for operation**

The mobile steam container MDC 2,600 is a ready-to-use, containerised steam unit for mobile use and self-sufficient operation.

The system is equipped with a water service module, Testomat, water sample cooling device and automatic dosage of chemicals. All our steam/hot water

systems are developed in accordance with state of-the-art technology and fitted with boilers and components by the Loos company. This allows us to guarantee reliable and environment-friendly operation. Our systems are checked and serviced on a regular basis.


Technical specifications / Accessories

Type	STEAMMASTER MDC 2.600
Heat output	500 - 1,700 kW (burner power)
Steam output	1,500 - 2,600 kg/h
Dimensions (L x W x H)	6,050 x 2,410 x 3,000 mm + additional 10' container for water treatment
Weight	12.500 kg (transport weight)
Power connection	400 V / CEE 63 A
Fuel	heating oil EL or natural gas H
Medium	Saturated steam approx. 200 °C
Response overpressure SV	16 bar
Boiler adjustment range	Pressure range 4,5 - 16 bar
Max. operating pressure	approx. 15 bar
Heating oil tank	external
Safety technology	TRD 604 / 72h / EN12953 Part 6
Frost protection	yes
Remote- / tank monitoring	Fault message connection potential-free
Flue system	stainless steel stack
Connection	Steam on site: DN125 / PN 40 Blow-down-pressure maintenance: DN25 / PN40

Areas of application:



Subject to technical changes - only for information



Accessories

	HOTTANK MHT 5.000 – 25.000 Mobile expansion tank up to 25,000 litres	HM2000000252
	HOTSILENCE MSD Silencer	HM2000000262
	FUEL MANAGEMENT We take care of: delivery and collection of the appropriate tank size, arrangement of filling, cleaning and emptying by a specialist company	HM2000001306