



Monobloc air conditioner

COOLMONO MRM 3

Artikelnr. Kauf: HM2000001295



Your advantages

- Cooling and heating in one device
- Flexible use in rooms up to 50 m²
- Simple handling
- Compact design
- Competitive acquisition price
- Operating mode – 230 V socket
- Quick and uncomplicated climate solution
- Exhaust air hose is included in the delivery

Mobile monobloc air conditioners are flexible and can be installed in any kind of room, at the condition that there is a possibility to run the exhaust air pipe to the outside.

Monobloc air conditioners ensure a comfortable


temperature in rooms up to 50 m². They are operated by electricity and plugged into a 230 V socket. The temperature can be set between 17 °C and 30 °C. The device offers different functions: cooling, heating, dehumidifying and air circulation.

Technical specifications / Accessories

Type	COOLMONO MRM 3
Cooling output	3,500 W (heat 3,000 W)
Dimensions (L x W x H)	467 x 397 x 765 mm
Weight	34 kg
Power connection	Schuko plug
Volume flow cold air	up to 386 m³/h
Refrigerant	R410A
Electrical power intake	max. 1,600 W / 8 A
Power	5.9 A (heat 5.0 A)
Electrical power supply	230 V / 50 Hz
Electrical connection	power cable with Schuko plug
Sound pressure level	65 db
Operating range	17 - 30 °C
Connection	exhaust air hose is included

Subject to technical changes - only for information

Areas of application:



Accessories



AIR CONDITIONING HOOD
for window blowing

Item number

HM2000006307