



# Split air-conditioning

## COOLSPLIT MSG 7

Artikelnr.: HM200000221



### Your advantages

- Latest technology
- Attractive design
- CE approved
- Nationwide Next-Day Express Delivery

This appliance, the SPLIT type, is a special air-conditioner where the heat conduction medium is a mixture of water and glycol. This enables the unit to cool at ambient temperatures up to -10 °C.

The internal unit is fitted with a rotating compressor, an expansion valve and a low pressure switch with automatic reset function. It is also equipped

with a high pressure switch, a water/refrigerant heat exchanger, a circulating water pump and a 5-stage fan. Other components include a defrosting thermostat, a thermostat for controlling room temperature, a condensate pump with tank and two level sensors (overflow control).

# Technical specifications / Accessories

Type	COOLSPLIT MSG 7
Cooling output	6.7 kW
Dimensions (L x W x H)	internal unit: 815 x 360 x 1,030 mm external unit: 582 x 360 x 460 mm
Weight	internal unit: 86 kg external unit: 16.5 kg
Refrigerant	R407C
Compressor	rotary piston
Maximum separation between internal and external unit	30m
Discharge heads	cooling water max.: 4m condensate max.: 1m
Electrical power intake	2.7 kW
power	12.0 A
Electrical power supply	230 V / 50 Hz / 1 Ph
Electrical connection	Schuko plugs
Sound pressure level	49 db(A)

Subject to technical changes - only for information

Areas of application:

