

## **Cooling unit** COOLUNIT MKZ 5 D

Artikelnr.: HM200000223



Your advantages

- Low noise level and best ESEER values
- Wide operating range
- Integrated hydronic module
- Simple plug-and-play installation

Air-cooled mini chiller with inverter. Inverter compressors continuously adjust the compressor speed to actual requirements. Less energy-consuming starts and stops lead to reduced energy consumption (up to 30%) and more stable temperatures. The scroll compressors consist of two scrolls, one is fixed while the other orbits eccentrically around it. Designed for small and medium capacities, they ensure reliable and high-efficiency operation constantly throughout their service life.

Single-phase power supply for residential applications, three-phase power supply for smaller commercial applications available.

## HOTMOBIL

## Technical specifications / Accessories

Туре	COOLUNIT MKZ 5 D	
Cooling output 7°/12° C and 32° C ambient temperature	8.77 kW	
Dimensions (L x W x H)	1,110 x 1,760 x 2,140 mm	
Weight	transport weight: 475 kg operating weight: 495 kg	
Refrigerant	R410A	
Compressor	Scroll	
Connection	Storz D (31KA)	
Electrical power intake	2.62 kW	
Power	27 A	
Electrical power supply	230 V / 50 Hz / 1 Ph	
Electrical connection	32 A / 230 V / ~1/N/PE	
Sound pressure level	at 1 m 51 db(A)	
Volumetric flow rate, water	max. 8 m <sup>3</sup> /h	
Discharge heads	max. 7 m	
Max. permitted system pressure	3 bar	

Areas of application:





Subject to technical changes - only for information

Accessories	Item number
HOTRAMP MÜR Mobile drive-over ramps made of robust hard rubber	HM200000289
COOLPUMP MKP The cold pump also for outdoor use	HM200000247
COOLAIR MLG 25 2,300 m <sup>3</sup> /h ventilation device, adjustable in five stages	HM200000234

