

Mobile accessories | Ventilation unit

COOLAIR MLG 25 EDV

ArtikelNr.: HM2000000235

Areas of application:



Type	COOLAIR MLG 25 EDV
Heat output	approx. 50 kW
Cooling output	16°C und 32°C ambient temperature: up to 25 kW
Dimensions (L x W x H)	800 x 680 x 1,890 mm
Weight	Transport / operating weight: 160 kg
Air power rating	2,300 m ³ /h
Water or glycol mixture	7 / 12°C
External pressure	200 Pa
Total pressure	450 Pa
Fan stages	5
Sound pressure level	at unit (outlet port): 83 db (A)
Motor output	1.5 kW
Mains voltage	230 V
Rated current	6.7 A
Electrical connection	Schuko plug
Connection	Storz D1"
Filter class	G4

Subject to technical changes - only for information

Your advantages

- **Down-flow design for EDP areas**
- **5-stage airflow control**
- **Narrow dimensions**
- **High air throughput up to 2,300 m³ / h**

2,300 m³/h Ventilation Unit, can be regulated in five stages with a pressure of up to 200 Pa. Particularly suitable for cooling server rooms, injecting air into raised floors.

Can also be used for heating storage halls, heating

of building sites, etc. in conjunction with a mobile heating unit or an existing block-type heating plant. The COOLAIR MLG 25 EDV fits through any standard door. The air exit is underneath the unit.