

# Mobile accessories | Ventilation unit

## COOLAIR MLG 50

Artikelnr.: HM2000000236

Areas of application:



Type	COOLAIR MLG 50
Cooling output	Air (32/13°C)/Water (7/12°C): up to 50 kW
Dimensions (L x W x H)	1.400 x 880 x 1,700 mm
Weight	transport weight: 350 kg operating weight: 390 kg
Cooling capacity	up to 5,000 m <sup>3</sup> /h
External pressure	200 Pa
Total pressure	537 Pa
Fan stages	5
Sound pressure level	at unit (outlet port): 80 db (A)
Motor output	1.5 kW
Mains voltage	400 V
Rated current	5.0 A
Electrical connection	16 A plug
Connection	Bauer 2"
Filter class	G4

Subject to technical changes - only for information

### Your advantages

- 5-stage airflow control
- Narrow dimensions
- Suitable for indoor and outdoor use
- High air throughput up to 5,000 m<sup>3</sup> / h

5,000 m<sup>3</sup>/h Ventilation Unit, can be regulated in five stages with a pressure of up to 200 Pa. Particularly suitable for cooling storage rooms, for event air-conditioning and machine cooling.

The COOLAIR MLG 50 is portable on castors and fits through any standard door. Air distribution via flexible air hose 1 x 500 mm or free outlet on 4 sides via air head.