

# Mobile accessories | Connection lines

## HOTFLEX MVL

Artikelnr.: HM2000000279

Areas of application:



Type	HOTFLEX MVL
<b>Hose material</b>	
Robust multi-purpose hoses for universal use	
Operating temperature	-40°C to +100°C
Operating pressure	10 bar at 100°C
Bursting pressure	30 bar at 20°C
<b>Hose material steam and condensate</b>	
High-pressure steam hose according to DIN EN ISO 6134 EPDM	
Operating temperature	up to +210°C
Operating pressure	18 bar max.
Bursting pressure	180 bar
With clamping jaw screw connection according to DIN 2826 up to 25 bar	
<b>Hose material domestic water HW / CW</b>	
Robust water hoses for domestic hot water	
Operating temperatures	-30°C to +100°C
Operating pressure	20 bar at 20°C
Bursting pressure	60 bar at 60°C
<b>Hose material for electric heating units</b>	
Robust water hoses	
Operating temperatures	-20°C to +100°C
Operating pressure	15 bar at 20°C
Bursting pressure	45 bar at 60°C

Subject to technical changes - only for information

Flexible, universal multi-purpose hoses for the connection of process, circulation and heating water as well as cooling.

As temporary bridging measures for renovation, repairs or interruptions due to defective pipelines