

Mobile accessories | System separator

HOTFLOW MST 500

ArtikelNr.: HM2000000243

Areas of application:



| Type | HOTFLOW MST 500 | |
|------------------------|-------------------------------|---------------|
| Transmission power | up to 500 kW | |
| | primary | secondary |
| Infeed temperature | 90° C | 65° C |
| Discharge temperature | 70° C | 85° C |
| Mass flow | 22,373 kg / h | 22,454 kg / h |
| Pressure loss | 22 kPa | ca. 70 kPa |
| Medium | heating water | |
| Connection | Storz C2" / Flansch DN50 PN16 | |
| Dimensions (L x W x H) | 1,200 x 600 x 1,350 mm | |
| Weight | Tare weight: approx. 230 kg | |

Subject to technical changes - only for information

Your advantages

- No problems at differing pressure conditions
- Suitable for outdoor use

Our mobile heat exchangers are suited for various purposes.

Installed in a steel frame and equipped with a tarpaulin cover, they can also be easily installed outdoors. Equipped with quick couplings, temperature control on the secondary side via digital controller,

temperature limiter, shut-offs, dirt traps, draining and venting as well as thermometer and manometer. Safety valves in 3 and 6 bar on the secondary side. Two plates form a channel. The media flow through these channels in counterflow manner (primary/secondary).